

LIKT40



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: ϕ 5X42PCS ,IR Distance:40M

Water resistance:IP66 Cable built-in bracket

3 Axis Bracket

Lens: 4-9mm Manual Zoom Lens

Dimension :228(W) x97(H) x82(D)mm



Specifications

Model	LIKT40SHE				
Image Sensor	1/3"SONY				
Horizontal Resolution	ICX673AK CCD,700TV Lines Low Illumination, Effio, WDR, OSD, NR				
Pixels	PAL:795 (H)× 596(V) NTSC :811 (H) × 508 (V)				
Usable Illumination	0.001Lux/F2.0				
TV System	PAL/NTSC				
IR LED	ϕ 5 X 42 PCS				
IR Series Distance	40 M				
Lens	4-9mm Manual Zoom Lens				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
IR Power On	CDS Auto Control				
S/N Ratio	\geq 48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max				
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max				
White Balance	Auto				
Power Source	DC12V 500mA				
Dimension	228(W) x97(H) x82(D)mm				
Weight	1600g				